




Specifications	LiFeBlue LB12200-HC
Capacity	200AH
Nominal Voltage	12.8 Volts
Full Charge Resting Voltage	13.32 Volts
Energy Storage	2600 Wh (2.6kWh)
Run Time @ 25 Amp Load	8 Hours @ 77°F (25°C)
Self Discharge Rate	7mA; Sleep 500µA
Wireless Data Communications	Bluetooth BLE, 4.0 or above
Charging	
Charging Temperature Range	32°F~119°F (140°F Max)
Charge Method	3 Stage or CC/CV
Absorb Voltage (Uo) (CV)	14.1 to 14.6 Volts
Float Voltage (I)	13.6 to 13.8 Volts
Maximum Current	150 Amps @ 75°F
Recommended Current	120 Amps
Recommended CV or Absorb Time	15 minutes
Charge Efficiency	99%
Discharging	
Discharge Temperature Range	-4°F~140°F (-20°C~60°C)
Discharge Current	150A, 200 for 30 Minutes
Discharge Current, 3 seconds	500 Amps
Discharge Cut Off Voltage	2.0 Volts, any cell (8 Volts)
Recommended Low Voltage Disconnect	11 Volts
Short Circuit Protection	850A for 500µs
Short Circuit Protection release	30 Seconds



Battery Protection	
BMS Control	PCM
Over Voltage, per cell, Open	3.8 Volts, ±0.03 Volts
Over Voltage, per cell, Release	3.6 Volts, ±0.05 Volts
Over Discharge, per cell, Open	2.0 Volts, ±0.05 Volts
Over Discharge, per cell, release	2.3 Volts, ±0.05 Volts
Over Current	>420 Amps; 6 Seconds
Over Current Release	30 Seconds
Over Temperature	149°F (65°C)
Over Temperature release	131°F
Low Temperature Charge Inhibit	32°F
Low Temperature Charge, Release	40°F
MOSFET Over Temperature, Open	212° F
MOSFET Over Temperature, Release	158° F
Mechanical	
Length	19-1/16"
Width	6-5/8"
Height	9-1/2"
Weight	56 Pounds (20 kg)
Hardware	M8 bolt, washer, lock washer
Hardware Torque	80 in-lb. (9 N-m)
Miscellaneous	
Packs in Parallel	4 (maximum recommended)
Packs in Series	4 Maximum
Discharge Test Setting	100% DoD @ 1C
Discharge Test Results	>2800 Cycles~83% remaining capacity
Storage Method	50% SoC, test @ 90 Days, recharge if below 13.0V
Recommended Storage temperature Range	-4°F~95°F (-20°C~35°C)
Lithium Ion Chemistry	Lithium Iron Phosphate (LFP; LiFePO4)
Cell Type	Prismatic Cells
Internal Impedance (50% SoC, 1kHz)	<20mΩ
Certifications	UL1642; IEC62133; TUV CB; CE; UN38.3; ISO9001-2009; ISO14001; OHSAS18001; TS16949

# LiFeBlue Battery

## Model LB12200-HC

LiFeBlue Battery (920) 543-3764 [www.lifebluebattery.com](http://www.lifebluebattery.com)